

FACTOR LED 3M 88200LM 840 90D DALI IP66 (651W) C5-M

DETAILED CARD



TECHNICAL PARAMETERS

Index:	682551
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	651
Luminous flux [lm]*:	88200
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

Factor Led C5-M (corrosion protection in harsh industrial and marine environments) is the latest generation of high-powered floodlight with impressive lumen output. It is characterised not only by very high luminous efficiency, but also by high IP66 sealing and IK09 impact resistance. These parameters were achieved thanks to the branded components used, the robust housing made of cast aluminium LM-6 (aluminium-silicon alloy) and the use of a passive lamp cooling system, which allows excess heat generation to be dissipated during lamp operation. In the C5-M version, the paint coating plays an even more important role. The Factor Led has the advantage of being very quick and easy to install. The lightweight steel arm is attached to the supporting structure (wall, column) and then the light modules are plugged in. On one bracket, the installer can plug in a lamp containing 1 to 4 such modules.

APPLICATION

Ports, wharves, shipyards, oil rigs and offshore infrastructure, chemical industry and refineries, bridges and infrastructure exposed to marine conditions, lighting on ships and ferries, industrial areas, playing fields, airports, car parks with high humidity and salinity.


FACTOR LED 3M 88200LM 840 90D DALI IP66 (651W) C5-M

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	651	LED lifespan L90B10 [h]:	47000
Index:	682551	Surge protection [kV]:	6
EAN:	5905963682551	Dimensions (H/W/T/S) [mm]:	580/425/340
Luminous flux [lm]:	88200	Material of the body:	aluminium
Light source:	LED module	Colour of the body:	RAL7016
Beam angle [°]:	90	Mounting dimensions [mm]:	310
Diffuser material:	PC	Impact resistance:	IK09
Version:	3 modules	Ingress protection:	IP66
Supply voltage [V]:	100-277	Mounting version:	top
Frequency [Hz]:	47-63	Working temperature [°C]:	from -40 to +45
Luminous efficacy [lm/W]:	135	Dimensions of single box [mm]:	430
Energy efficiency class:	D	Number on the palette [pcs]:	18
Electrical protection class:	I	Net weight [kg]:	16.980
Colour temperature [K]:	4000	Light distribution type:	symmetric
Colour rendering index:	>80	Corrosivity category:	C5-M
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.97	CE certificate:	262/2023
LED lifespan L70B50 [h]:	156000	ENEC Certificate:	0404/ENEC/25
DIMM DALI:	yes	Manual:	Download PDF
LED lifespan L80B20 [h]:	98000		

LIGHT CURVES



Card creation date: 19 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 262/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl