

FACTOR LED HB 1M 29000LM 740 120D DALI IP66 SH (233W) C5-M

DETAILED CARD



TECHNICAL PARAMETERS

Index:	682896
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	233
Luminous flux [lm]*:	29000
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
SDCM:	5
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

Factor Led HB C5-M (corrosion protection in harsh industrial and marine environments) is the latest generation of high bay with high power and high lumen output. It is characterised not only by very high luminous efficacy, but also by high IP66 sealing and IK09 impact resistance. These parameters are achieved thanks to the branded components used, the robust housing made of cast aluminium LM-6 (aluminium-silicon alloy) and the use of a passive lamp cooling system, which allows excess heat generation to be dissipated during lamp operation. In the C5-M version, the paint coating plays an even more important role. The Factor Led has the advantage of being very quickly and easily suspended or surface-mounted. The design allows the hanging or mounting of a lamp consisting of one or two light modules.

APPLICATION

Ports, wharves, shipyards, oil rigs and offshore infrastructure, chemical industry and refineries, bridges and infrastructure exposed to marine conditions, lighting on ships and ferries, industrial areas, playing fields, airports, car parks with high humidity and salinity.


FACTOR LED HB 1M 29000LM 740 120D DALI IP66 SH (233W) C5-M

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	682896	Colour of the body:	RAL7016
EAN:	5905963682896	Dimensions (H/W/T/S) [mm]:	191/397/125
Rated power of the luminaire [W]:	233	Mounting dimensions [mm]:	357/77
Luminous flux [lm]:	29000	Impact resistance:	IK09
Supply voltage [V]:	220-240	Ingress protection:	IP66
Luminous efficacy [lm/W]:	124	Mounting version:	surface-mounted or suspended
Energy efficiency class:	D	Working temperature [°C]:	from -40 to +45
Electrical protection class:	I	DIMM DALI:	yes
Colour temperature [K]:	4000	Dimensions of single box [mm]:	430
Color rendering index (Ra) >:	70	Number on the palette [pcs]:	35
SDCM:	5	Net weight [kg]:	4.720
Power factor:	0.98	Version:	1 module
LED lifespan L70B50 [h]:	156000	Corrosivity category:	C5-M
LED lifespan L80B10 [h]:	98000	Warranty [years]:	5
LED lifespan L90B10 [h]:	47000	CE certificate:	263/2023
Beam angle [°]:	120	ENEC Certificate:	0404/ENEC/25
Surge protection [kV]:	6	Environmental Product Declaration (EPD):	816/2025
Diffuser material:	tempered glass	Manual:	Download PDF
Diffuser type:	transparent	Plik LDT:	Download
Material of the body:	aluminium		

LIGHT CURVES



Card creation date: 19 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 263/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl