

SOLANTO QUATTRO MULTI Z 2X600MM+2X900MM 8160-14400LM 840 IP20 I CL. OPAL BLACK 120-212W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-------------------------|
| Light source: | LED module |
| Rated power [W] - range: | 120-212 |
| Luminous flux of the luminaire [lm] - range: | 8160-14400 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| Diffuser type: | OPAL |
| Colour of the body: | black |
| Dimensions (H/W/T/S) [mm]: | 2x Ø 900/32.2x Ø 602/32 |
| Mounting version: | suspended |

CHARACTERISTICS

A suspended LED lamp made up of two rings of 602mm diameter and two rings of 900mm diameter, allowing for an attractive arrangement of representative interiors. The lamp is made of powder-coated steel in white, black or any other colour to match the character of the interior. The thermoformed milk shades emphasise the decorative character of the lamp. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings, increasing the versatility and functionality of the lamp while keeping the number of indexes to a minimum.

APPLICATION

Solanto Quattro is an extremely impressive pendant lamp, dedicated to interiors such as lobbies, receptions, shopping malls and showrooms. It is also perfect for flats and flats, blending in perfectly with stylish surroundings.

SOLANTO QUATTRO MULTI Z 2X600MM+2X900MM 8160-14400LM 840 IP20 I CL. OPAL BLACK 120-212W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|---|--|---------------------------------------|------------------------------|
| Index: | 467462 | Ring material: | Steel |
| EAN: | 5905963467462 | LED lifespan L90B10 [h]: | 35700 |
| Category of application: | architectural, HoReCa, art and culture | Efficiency of the luminaire: | 0.80 |
| Rated power [W] - range: | 120-212 | Diffuser type: | OPAL |
| Light source: | LED module | Diffuser material: | PMMA |
| Luminous flux of the luminaire [lm] - range: | 8160-14400 | Colour of the body: | black |
| Supply voltage [V]: | 220-240 | Diffuser colour: | milky |
| Frequency [Hz]: | 50-60 | Dimensions (H/W/T/S) [mm]: | 2x Ø 900/32.2x Ø 602/32 |
| Colour temperature [K]: | 4000 | Material of the body: | Steel |
| Luminous efficacy [lm/W]: | 68 | Ingress protection: | IP20 |
| Energy efficiency class: | G | Mounting version: | suspended |
| Electrical protection class: | I | Cable length [m]: | 1.20 |
| Colour rendering index: | >80 | Dimensions of single box [mm]: | 903/903/108 x2 |
| SDCM: | ≤ 3 | Number on the palette [pcs]: | 1 |
| Power factor: | 0.90 | Warranty [years]: | 5 |
| LED lifespan L70B50 [h]: | 116600 | CE certificate: | 12/2025 |
| LED lifespan L80B20 [h]: | 73600 | Manual: | Download PDF |

Card creation date: 20 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 12/2025