

LUMAX S LED

DETAILED CARD



TECHNICAL PARAMETERS

Index:	323829
Ingress protection:	IP40
Nominal power [W]:	2
Diffuser material:	PC
Diffuser type:	PRM
Emergency lighting [h]:	3
Working temperature [°C]:	from 0 to +35
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	350/120/75

CHARACTERISTICS

Surface mounted, universal (maintained or non-maintained system) emergency fitting with a low profile including an integrated, energy-saving LED GO! light source with a power of 2W. Body made of plastic, grey; prismatic polycarbonate (PC) diffuser. NiCd battery with manual testing function included; battery life in the event of emergency is 3h. Usable visibility of exit signs – up to 20 meters.

APPLICATION

Autonomous emergency fitting, dedicated for illumination of evacuation routes and emergency exits in the event of voltage drop in the power grid, i.e. in emergency mode. Product intended for surface mounting walls. Recommended particularly for areas of technical nature (passageways, staircases, garages, cellars) and for all applications which require the installation of permanent emergency lighting.

LUMAX S LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	2	Mounting version:	surface
Light source:	LED module	Working temperature [°C]:	from 0 to +35
Diffuser type:	PRM	Net weight [kg]:	0.800
Emergency lighting [h]:	3	CE certificate:	67/2020
Supply voltage [V]:	220-240	Warranty [years]:	2 / 0.5 (bateria)
Frequency [Hz]:	50 - 60	Index:	323829
Electrical protection class:	II	EAN:	5905963323829
LED lifespan L70B50 [h]:	50000	Category type:	emergency lighting
Beam angle [°]:	120	ETIM class:	EC001957
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	350/120/75	Manual:	Download PDF
Ingress protection:	IP40		

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 67/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl