

# LUMAX S LED

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	323829
<b>Ingress protection:</b>	IP40
<b>Nominal power [W]:</b>	2
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PRM
<b>Emergency lighting [h]:</b>	3
<b>Working temperature [°C]:</b>	from 0 to +35
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	350/120/75

## CHARACTERISTICS

Surface mounted, universal (maintained or non-maintained system) emergency fitting with a low profile including an integrated, energy-saving LED GO! light source with a power of 2W. Body made of plastic, grey; prismatic polycarbonate (PC) diffuser. NiCd battery with manual testing function included; battery life in the event of emergency is 3h. Usable visibility of exit signs – up to 20 meters.

## APPLICATION

Autonomous emergency fitting, dedicated for illumination of evacuation routes and emergency exits in the event of voltage drop in the power grid, i.e. in emergency mode. Product intended for surface mounting walls. Recommended particularly for areas of technical nature (passageways, staircases, garages, cellars) and for all applications which require the installation of permanent emergency lighting.

# LUMAX S LED

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Light source:</b>	LED module	<b>Working temperature [°C]:</b>	from 0 to +35
<b>Nominal power [W]:</b>	2	<b>Emergency lighting [h]:</b>	3
<b>Supply voltage [V]:</b>	220-240	<b>Net weight [kg]:</b>	0.800
<b>Frequency [Hz]:</b>	50 - 60	<b>CE certificate:</b>	<a href="#">67/2020</a>
<b>Electrical protection class:</b>	II	<b>Warranty [years]:</b>	2 / 0.5 (bateria)
<b>LED lifespan L70B50 [h]:</b>	50000	<b>Index:</b>	323829
<b>Beam angle [°]:</b>	120	<b>EAN:</b>	5905963323829
<b>Diffuser material:</b>	PC	<b>Category type:</b>	emergency lighting
<b>Diffuser type:</b>	PRM	<b>ETIM class:</b>	EC001957
<b>Dimensions (H/W/T/S) [mm]:</b>	350/120/75	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Ingress protection:</b>	IP40	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Mounting version:</b>	surface		

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 67/2020