

DOT CSC LED EVO 3W 450LM HB IP65 3H NM AT

DETAILED CARD



TECHNICAL PARAMETERS

Index:	233760
Ingress protection:	IP65
Impact resistance:	IK07
Rated power of the luminaire [W]*:	3
Luminous flux [lm]*:	450
Colour temperature [K]:	4000
Material of the body:	PC
Diffuser material:	PMMA
Diffuser type:	lens
Optics material:	PC

CHARACTERISTICS

Surface-mounted 3W standalone emergency luminaire with an integrated, energy-efficient LED light module with 450lm light output. Body made of polycarbonate (PC). Optics available in 4 variants: general wide, general narrow, corridor wide, corridor narrow. DOT LED EVO has a built-in Li-ion battery, with an emergency operating time of 1h or 3h. The luminaire is available in an autotest (AT) version. Available in white or black.

APPLICATION

A self-contained emergency luminaire whose main use is to illuminate escape routes and fire protection equipment following a mains power failure. Particularly recommended where it is necessary to install emergency lighting as part of the modernisation of an existing installation. It successfully replaces lamps with a built-in emergency module. Thanks to additional sealing, the luminaire achieves IP65 sealing and can be used in areas with increased humidity or outdoors under cover.


DOT CSC LED EVO 3W 450LM HB IP65 3H NM AT

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	233760	Dimensions (H/W/T/S) [mm]:	ø140/40
Light source:	LED module	Mounting dimensions [mm]:	104
Rated power of the luminaire [W]:	3	Impact resistance:	IK07
Supply voltage [V]:	230	Ingress protection:	IP65
Frequency [Hz]:	50-60	Mounting version:	surface
Luminous flux [lm]:	450	Working temperature [°C]:	from +5 to +35
Luminous efficacy [lm/W]:	150	Emergency lighting [h]:	3
Colour temperature [K]:	4000	Net weight [kg]:	0.250
LED lifespan L70B50 [h]:	167000	Category type:	emergency lighting
Beam angle [°]:	CSCHB	Autotest:	yes
Exchangeable source:	yes	Operating mode:	NM
Battery:	Li-Ion	LED lifespan L80B20 [h]:	101000
Battery capacity [mAh]:	4000	LED lifespan L90B10 [h]:	49500
Diffuser material:	PMMA	Light distribution type:	corridor narrow
Diffuser type:	lens	Warranty [years]:	5
Diffuser colour:	transparent	CE certificate:	41/2025
Optics material:	PC	Manual:	Download PDF
Material of the body:	PC	Plik LDT:	Download
Colour of the body:	white		

LIGHT CURVES



DOT CSC LED EVO 3W 450LM HB IP65 3H NM AT

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
545672	DOT CS galvanized steel arm
551161	Ceiling spacer DOT white matt



DOT CS galvanized steel arm (545672)



Ceiling spacer DOT white matt (551161)

Card creation date: 20 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 41/2025