

GAMMA LED 280 1500LM 830 IP54 II CL. OPAL (12W) 280MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	191220
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	12
Luminous flux [lm]*:	1500
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

The latest version of the popular plafond - even better performance, same proven quality.

Surface-mounted, round LED light fitting with a luminous flux of 87 lm/W, ingress protection class IP54 and an integrated energy-saving light source LED. White base; diffuser made of impact-resistant PC provides even light distribution and ensures a high impact resistance class (IK10).

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.

GAMMA LED 280 1500LM 830 IP54 II CL. OPAL (12W)


280MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	191220	Optics material:	PC
EAN:	5905963191220	Material of the body:	PP
Light source:	LED module	Colour of the body:	white
Nominal power [W]:	12	Dimensions (H/W/T/S) [mm]:	ø280/72
Rated power of the luminaire [W]:	12	Mounting dimensions [mm]:	160
Supply voltage [V]:	220-240	Impact resistance:	IK10
Luminous flux [lm]:	1500	Ingress protection:	IP54
Luminous efficacy [lm/W]:	125	Mounting version:	surface
Energy efficiency class:	E	Working temperature [°C]:	from -20 to +25
Electrical protection class:	II	Dimensions of single box [mm]:	280
Colour temperature [K]:	3000	Net weight [kg]:	0.430
Color rendering index (Ra) >:	80	Category type:	bulkheads
SDCM:	3	Light distribution type:	open space
Power factor:	0.90	Warranty [years]:	5
LED lifespan L70B50 [h]:	119000	CE certificate:	43/2025
Beam angle [°]:	120	PZH certificate:	B-BK-60112-0232/2025
Surge protection [kV]:	1	Environmental Product Declaration (EPD):	944/2026
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	OPAL	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Diffuser colour:	white	Plik LDT:	Download

LIGHT CURVES



GAMMA LED 280 1500LM 830 IP54 II CL. OPAL (12W) 280MM

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
-------	------

Card creation date: 24 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 43/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl