

# TERRACO DIR LED ALU 640LM PLX IP54 I CL. 840 17W BLACK

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	774058
Light source:	LED module
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	640
Energy efficiency class:	B
Electrical protection class:	I
Colour temperature [K]:	4000
Colour rendering index:	80
Exchangeable source:	yes
Material of the body:	aluminium

## CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

## APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.

# TERRACO DIR LED ALU 640LM PLX IP54 I CL. 840 17W


## BLACK

DETAILED CARD


### TECHNICAL PARAMETERS TABLE

Index:	774058	Exchangeable source:	yes
EAN:	5905963774058	Diffuser material:	PMMA
Light source:	LED module	Diffuser type:	matt
Rated power of the luminaire [W]:	17	Diffuser colour:	white
Luminous flux [lm]:	640	Material of the body:	aluminium
Frequency [Hz]:	50-60	Colour of the body:	black
Luminous efficacy [lm/W]:	39	Dimensions (H/W/T/S) [mm]:	260/110/100
Energy efficiency class:	B	Impact resistance:	IK04
Electrical protection class:	I	Ingress protection:	IP54
Colour temperature [K]:	4000	Mounting version:	surface
Colour rendering index:	80	Working temperature [°C]:	from -25 to +35
SDCM:	≤ 4	Supply voltage [V]:	220 - 240
LED lifespan L70B50 [h]:	134000	Warranty [years]:	5
LED lifespan L80B20 [h]:	86000	CE certificate:	<a href="#">90/2025</a>
LED lifespan L90B10 [h]:	46000	Manual:	<a href="#">Download PDF</a>
Light distribution type:	DIR	Plik LDT:	<a href="#">Download</a>
Optics:	general		

### TECHNICAL DETAILS



Dir



Dir