## TERRACO FRONT LED ALU 630LM PLX IP54 I CL. 840 17W GREY

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index: 774133

**Light source:** LED module

Rated power of the luminaire [W]\*: 17

Luminous flux [lm]\*: 630

Energy efficiency class: G

Electrical protection class:

Colour temperature [K]: 4000

Color rendering index (Ra) >: 80

Exchangeable source: yes

Material of the body: aluminium

#### **CHARACTERISTICS**

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

#### **APPLICATION**

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.



# TERRACO FRONT LED ALU 630LM PLX IP54 I CL. 840 17W GREY


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	774133
EAN:	5905963774133
Light source:	LED module
Rated power of the luminaire [W]:	17
Luminous flux [Im]:	630
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	39
Energy efficiency class:	G
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	4
LED lifespan L70B50 [h]:	134000
LED lifespan L80B20 [h]:	86000
LED lifespan L90B10 [h]:	46000
Light distribution type:	FRONT
Optics:	general
	-

Exchangeable source:	yes
Diffuser material:	PMMA
Diffuser type:	matt
Diffuser colour:	white
Material of the body:	aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	260/110/100
Impact resistance:	IK04
Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -25 to +35
Supply voltage [V]:	220 - 240
Warranty [years]:	5
CE certificate:	90/2025
Manual:	Download PDF
Category of application:	architectural
Plik LDT:	<u>Download</u>

#### **TECHNICAL DETAILS**



Front

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

