

# TERRACO FRONT LED ALU 630LM PLX IP54 I CL. 840 17W GREY

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	774133
<b>Light source:</b>	LED module
<b>Rated power of the luminaire [W]*:</b>	17
<b>Luminous flux [lm]*:</b>	630
<b>Energy efficiency class:</b>	G
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Exchangeable source:</b>	yes
<b>Material of the body:</b>	aluminium

## CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

## APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.


# TERRACO FRONT LED ALU 630LM PLX IP54 I CL. 840 17W GREY

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	774133	<b>Exchangeable source:</b>	yes
<b>EAN:</b>	5905963774133	<b>Diffuser material:</b>	PMMA
<b>Light source:</b>	LED module	<b>Diffuser type:</b>	matt
<b>Rated power of the luminaire [W]:</b>	17	<b>Diffuser colour:</b>	white
<b>Luminous flux [lm]:</b>	630	<b>Material of the body:</b>	aluminium
<b>Frequency [Hz]:</b>	50-60	<b>Colour of the body:</b>	gray RAL 9006
<b>Luminous efficacy [lm/W]:</b>	39	<b>Dimensions (H/W/T/S) [mm]:</b>	260/110/100
<b>Energy efficiency class:</b>	G	<b>Impact resistance:</b>	IK04
<b>Electrical protection class:</b>	I	<b>Ingress protection:</b>	IP54
<b>Colour temperature [K]:</b>	4000	<b>Mounting version:</b>	surface
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Working temperature [°C]:</b>	from -25 to +35
<b>SDCM:</b>	4	<b>Supply voltage [V]:</b>	220 - 240
<b>LED lifespan L70B50 [h]:</b>	134000	<b>Warranty [years]:</b>	5
<b>LED lifespan L80B10 [h]:</b>	86000	<b>CE certificate:</b>	<a href="#">90/2025</a>
<b>LED lifespan L90B10 [h]:</b>	46000	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Light distribution type:</b>	FRONT	<b>Category of application:</b>	architectural
<b>Optics:</b>	general	<b>Plik LDT:</b>	<a href="#">Download</a>

## TECHNICAL DETAILS



Front

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 90/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl