# TERRACO FRONT LED ALU 630LM PLX IP54 I CL. 840 17W GREY

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 774133 |
| **Light source:** | LED module |
| **Rated power of the luminaire [W]*:** | 17 |
| **Luminous flux [lm]*:** | 630 |
| **Energy efficiency class:** | G |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **Exchangeable source:** | yes |
| **Material of the body:** | aluminium |

## CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

## APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.

# TERRACO FRONT LED ALU 630LM PLX IP54 I CL. 840 17W GREY


DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 774133 |
| **EAN:** | 5905963774133 |
| **Light source:** | LED module |
| **Rated power of the luminaire [W]:** | 17 |
| **Luminous flux [lm]:** | 630 |
| **Frequency [Hz]:** | 50-60 |
| **Luminous efficacy [lm/W]:** | 39 |
| **Energy efficiency class:** | G |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **SDCM:** | 4 |
| **LED lifespan L70B50 [h]:** | 134000 |
| **LED lifespan L80B10 [h]:** | 86000 |
| **LED lifespan L90B10 [h]:** | 46000 |
| **Light distribution type:** | FRONT |
| **Optics:** | general |

| | |
|---|---|
| **Exchangeable source:** | yes |
| **Diffuser material:** | PMMA |
| **Diffuser type:** | matt |
| **Diffuser colour:** | white |
| **Material of the body:** | aluminium |
| **Colour of the body:** | gray RAL 9006 |
| **Dimensions (H/W/T/S) [mm]:** | 260/110/100 |
| **Impact resistance:** | IK04 |
| **Ingress protection:** | IP54 |
| **Mounting version:** | surface |
| **Working temperature [°C]:** | from -25 to +35 |
| **Supply voltage [V]:** | 220 - 240 |
| **Warranty [years]:** | 5 |
| **CE certificate:** | 90/2025 |
| **Manual:** | Download PDF |
| **Category of application:** | architectural |
| **Plik LDT:** | Download |

## TECHNICAL DETAILS



Front

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 90/2025

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl