

TERRACO SIDE DIR LED ALU 240LM PLX IP54 I CL. 840 8W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|------------|
| Index: | 774201 |
| Light source: | LED module |
| Rated power of the luminaire [W]*: | 8 |
| Luminous flux [lm]*: | 240 |
| Energy efficiency class: | G |
| Electrical protection class: | I |
| Colour temperature [K]: | 4000 |
| Color rendering index (Ra) >: | 80 |
| Exchangeable source: | yes |
| Material of the body: | aluminium |

CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.


TERRACO SIDE DIR LED ALU 240LM PLX IP54 I CL. 840 8W BLACK

DETAILED CARD


TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|----------------------------|------------------------------|
| Index: | 774201 | Exchangeable source: | yes |
| EAN: | 5905963774201 | Diffuser material: | PMMA |
| Light source: | LED module | Diffuser type: | matt |
| Rated power of the luminaire [W]: | 8 | Diffuser colour: | white |
| Luminous flux [lm]: | 240 | Material of the body: | aluminium |
| Frequency [Hz]: | 50-60 | Colour of the body: | black |
| Luminous efficacy [lm/W]: | 32 | Dimensions (H/W/T/S) [mm]: | 260/110/100 |
| Energy efficiency class: | G | Impact resistance: | IK04 |
| Electrical protection class: | I | Ingress protection: | IP54 |
| Colour temperature [K]: | 4000 | Mounting version: | surface |
| Color rendering index (Ra) >: | 80 | Working temperature [°C]: | from -25 to +35 |
| SDCM: | 4 | Supply voltage [V]: | 220 - 240 |
| LED lifespan L70B50 [h]: | 134000 | Warranty [years]: | 5 |
| LED lifespan L80B20 [h]: | 86000 | CE certificate: | 90/2025 |
| LED lifespan L90B10 [h]: | 46000 | Manual: | Download PDF |
| Light distribution type: | SIDE DIR | Category of application: | architectural |
| Optics: | general | Plik LDT: | Download |

TECHNICAL DETAILS



Side



Side

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 90/2025

 **LENA**
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl