

# TIARA 2 LED S 15000LM 740 RM7HE IP66 II CL. DALI IK09 (99W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	862274
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	99
<b>Luminous flux [lm]*:</b>	15000
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	> 70
<b>Electrical protection class:</b>	II
<b>Optics:</b>	RM7HE

## CHARACTERISTICS

TIARA 2 LED a new generation of LED road luminaires. It uses directional multi-lens arrays made of PMMA, with each lens having the same optics, ensuring that the light characteristics remain constant over time. The luminaire's dual-chamber design maintains the integrity of the optical chamber during installation work and the opening of the electrical chamber. As standard, the luminaire offers tool-free access to the electrical fixtures using two independent clips, which, if desired and needed to protect against vandalism or uncontrolled opening, can optionally be permanently secured with screws or a seal. The upper part of the luminaire, has dedicated hinges and a safety cable to prevent falling. Using standard tools, quick and convenient service is possible, allowing replacement of any component without the need to disassemble the entire fixture and make soldered connections. The body and handle made of die-cast aluminum, powder-coated in gray, is characterized by a very high degree of IP66 and IK10 impact resistance. Standard features: ergonomic light module suspension system; NTC luminaire accidental overheating protection; fully programmable DALI driver; available functions for maintaining constant lumen output during CLO and autonomous 5-stage power reduction; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; anti-vandal protection with screws/seal; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnect switch that disconnects voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL color. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

## APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.


# TIARA 2 LED S 15000LM 740 RM7HE IP66 II CL. DALI IK09 (99W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	862274	Optics material:	PMMA + PC
Rated power of the luminaire [W]:	99	Exchangeable source:	yes
EAN:	5905963862274	Material of the body:	powder coated aluminium
Luminous flux [lm]:	15000	Colour of the body:	grey
ETIM class:	EC000062	Dimensions (H/W/T/S) [mm]:	424/251/105
Luminous efficacy [lm/W]:	152	Mounting dimensions [mm]:	ø60
Category type:	street lighting	Impact resistance:	IK10
Energy efficiency class:	C	Ingress protection:	IP66
Product line:	HE	Mounting version:	Top, on pole / Side, on boom
Colour temperature [K]:	4000	Tilt angle adjustment [°]:	-30° to +120° (peak); -120° to +30° (side)
Version:	S	Lateral surface (SCx) [m2]:	0.021
Colour rendering index:	> 70	Working temperature [°C]:	from -40 to +50
Light source:	LED module	Control:	Yes + 5-stage power reduction
Electrical protection class:	II	Protection type:	NTC + ESD
Optics:	RM7HE	Vandalproof:	yes
Supply voltage [V]:	220 - 240	Net weight [kg]:	4.340
DIMM DALI:	yes	ENEC Certificate:	<a href="#">0410/ENEC/25; 0141/ENEC+/25</a>
Frequency [Hz]:	50 - 60	CE certificate:	<a href="#">91/2023</a>
SDCM:	≤ 5	Zhaga-D4i:	<a href="#">ZG407220042023</a>
Surge protection [kV]:	10	Environmental Product Declaration (EPD):	<a href="#">682/2024</a>
Diffuser material:	toughened glass	Manual:	<a href="#">Download PDF</a>
Diffuser type:	transparent		

## LIGHT CURVES



# TIARA 2 LED S 15000LM 740 RM7HE IP66 II CL. DALI IK09 (99W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL01350	Handle fi 76mm for Tiara 2 LED M and Tiara 2 LED S
813443	Backshield P (right) Tiara 2 LED S RAL9006
813450	Backshield L (left) Tiara 2 LED S RAL9006
813436	Backshield T (back) Tiara 2 LED S RAL9006



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 07 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 91/2023