STRADO LED XS 4850LM 740 RM7HE IP66 II CL. DALI IK10 (29W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	841132
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	29
Luminous flux [lm]*:	4850
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
Electrical protection class:	II
Optics:	RM7HE

5-stage power reduction

CHARACTERISTICS

Strado LED XS is a new family of LED road luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and state-of-the-art LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 155 lm/W. The upper part of the body has a separate electrical cavity in the body, which allows for efficient cooling of all power supply components, independently of the light module. The lower surface of the luminaire is finished entirely with toughened glass, providing high aesthetic qualities. The luminaire has an outgoing cable with quick-release connector, which allows fast, convenient and reliable installation without opening the luminaire. Using standard tools, it is possible to service the luminaire, allowing any component to be replaced without soldering. The body and fixture are made of die-cast aluminium, powder-coated grey, and have a very high P66 ingress protection rating and IKO9, IK10 mechanical impact resistance. Standard features: fully programmable DALI driver; available functions for maintaining constant luminous flux during CLO and autonomous 5-step power reduction; NTC protection against accidental overheating of the luminaire; filter to prevent condensation; outgoing cable with quick-connector. Additional options: NEMA, ZHAGA connectors on the top of the luminaire; interfacing with control systems; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; painting in any RAL colour. Certifications: CE, Zhaga D4i, ENEC, ENEC+.

APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.



Control:

STRADO LED XS 4850LM 740 RM7HE IP66 II CL. DALI IK10 (29W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	841132
EAN:	5905963841132
Category type:	street lighting
Version:	XS
Light source:	LED module
Rated power of the luminaire [W]:	29
Supply voltage [V]:	220 – 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	4850
Luminous efficacy [lm/W]:	167
Energy efficiency class:	В
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
Diffuser material:	tempered glass
Diffuser type:	transparent
Optics material:	PMMA + PC
Optics:	RM7HE
Material of the body:	powder coated aluminium
Colour of the body:	gray RAL 9006
Dimensions (H/W/T/S) [mm]:	449/185/85

Mounting dimensions [mm]:	ø48-60	
Impact resistance:	IK10	
•		
Ingress protection:	IP66	
Mounting version:	Top, on pole / Side, on boom	
Tilt angle adjustment [°]:	-20 to +20	
Lateral surface (SCx) [m2]:	0.018	
Working temperature [°C]:	from -40 to +50	
DIMM DALI:	yes	
Control:	5-stage power reduction	
Protection type:	NTC	
Net weight [kg]:	3.500	
ULOR:	0%	
Photobiological safety:	RG0 - exempt (no photobiological hazard)	
Technical Warranty:	5 with the possibility of extension to 10	
ENEC Certificate:	0390/ENEC/24; 0133/ENEC+/24	
CE certificate:	76/2024	
Zhaga-D4i:	ZG436418112024	
Environmental Product Declaration (EPD):	682/2024	
Manual:	Download PDF	
LED lifespan L95B10 [h]:	100000	

LIGHT CURVES





STRADO LED XS 4850LM 740 RM7HE IP66 II CL. DALI IK10 (29W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
842160	Backshield T (back) Strado LED XS RAL9006
842177	Backshield P (right) Strado LED XS RAL9006
842184	Backshield L (left) Strado LED XS RAL9006





wall holder (galvanized) (314049)

wall holder (grey) (314056)