STRADO LED S 13225LM 740 RM7HE IP66 II CL. DALI IK10 (84W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	841583
--------	--------

Ingress protection: IP66

Impact resistance: IK10

Rated power of the luminaire [W]*: 84

Luminous flux [lm]*: 13225

Colour temperature [K]: 4000

Color rendering index (Ra) >: 70

Electrical protection class:

Optics: RM7HE

Control: 5-stage power reduction

CHARACTERISTICS

STRADO LED is a new family of LED road luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and state-of-the-art LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 165 lm/W. The upper part of the body has a separate electrical cavity in the body, which allows for efficient cooling of all power supply components, independently of the light module. The lower surface of the luminaire is finished entirely with toughened glass, providing high aesthetic qualities. The luminaire has an outgoing cable with a quick-release connector, which allows fast, convenient and reliable installation without opening the luminaire. Using standard tools, it is possible to service the luminaire, allowing any component to be replaced without soldering. The body and fixture are made of die-cast aluminium, powder-coated grey, and have a very high 1966 ingress protection rating and IK10 mechanical impact resistance. Standard features: fully programmable DALI driver; available functions for maintaining constant luminous flux during CLO and autonomous 5-step power reduction; NTC protection against accidental overheating of the luminaire; filter to prevent condensation; outgoing cable with quick-connector. Additional options: NEMA, ZHAGA connectors on the top of the luminaire; interfacing with control systems; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; painting in any RAL colour. Certifications: CE, ROHS, ENEC, ENEC+, Zhaga D4i.

APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.



STRADO LED S 13225LM 740 RM7HE IP66 II CL. DALI IK10 (84W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	841583
EAN:	5905963841583
Category type:	street lighting
Version:	S
Light source:	LED module
Rated power of the luminaire [W]:	84
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	13225
Luminous efficacy [lm/W]:	157
Energy efficiency class:	В
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
SDCM:	5
Surge protection [kV]:	10
Diffuser material:	tempered glass
Diffuser type:	transparent
Optics material:	PMMA + PC
Optics:	RM7HE
Material of the body:	powder coated aluminium
Colour of the body:	gray RAL 9006
Dimensions (H/W/T/S) [mm]:	385/265/60

Mounting dimensions [mm]:	ø48-60
Impact resistance:	IK10
Ingress protection:	IP66
Mounting version:	Top, on pole / Side, on boom
Tilt angle adjustment [°]:	-20 to +20
Lateral surface (SCx) [m2]:	0.018
Working temperature [°C]:	from -40 to +50
LED lifespan L90B10 [h]:	100000
DIMM DALI:	yes
Control:	5-stage power reduction
Protection type:	NTC + ESD
Net weight [kg]:	4.440
Wire type:	HO7 RNF-2x1
ULOR:	0%
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Technical Warranty:	5 with the possibility of extension to 10
ENEC Certificate:	0390/ENEC/24; 0133/ENEC+/24
CE certificate:	<u>85/2023</u>
Zhaga-D4i:	ZG415127092023
Environmental Product Declaration (EPD):	682/2024
Manual:	Download PDF
Product line:	HE

LIGHT CURVES





STRADO LED S 13225LM 740 RM7HE IP66 II CL. DALI IK10 (84W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
842139	Backshield T (back) Strado LED S RAL9006
842146	Backshield P (right) Strado LED S RAL9006
842153	Backshield L (left) Strado LED S RAL9006





wall holder (galvanized) (314049)

wall holder (grey) (314056)

