

LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 NT BLACK 830 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779008
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Colour rendering index:	<80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($R_a \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 NT BLACK 830 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779008	Optics:	reflector
Rated power of the luminaire [W]:	12	Material of the body:	aluminium
EAN:	5905963779008	Ring colour:	black
Colour temperature [K]:	3000	Wire type:	czarny oplot
Light source:	LED	Ring material:	aluminium
Luminous flux [lm]:	1280	Control:	ON/OFF
Supply voltage [V]:	230	Dimensions (H/W/T/S) [mm]:	fi=60 L=170
Frequency [Hz]:	50-60	Mounting dimensions [mm]:	L= 40mm fi6mm
Luminous efficacy [lm/W]:	90	Ingress protection:	IP20
Electrical protection class:	I	Mounting version:	surface
Energy efficiency class:	E	Cable length [m]:	1.50
Beam angle [°]:	20	Dimensions of single box [mm]:	fi=70mm L=200mm
Colour rendering index:	<80	LED lifespan L90B10 [h]:	60000
Light colour:	ciepła biel	CE certificate:	51/2025
Exchangeable source:	yes	Manual:	Download PDF
Optics material:	aluminium		
Colour of the body:	black		

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl