

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 NT SILVER 830 (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	779060
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Colour rendering index:	<80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	silver

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ( $Ra \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 NT SILVER 830 (12W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	779060	<b>Optics:</b>	reflector
<b>Rated power of the luminaire [W]:</b>	12	<b>Material of the body:</b>	aluminium
<b>EAN:</b>	5905963779060	<b>Ring colour:</b>	silver
<b>Colour temperature [K]:</b>	3000	<b>Wire type:</b>	czarny oplot
<b>Light source:</b>	LED	<b>Ring material:</b>	aluminium
<b>Luminous flux [lm]:</b>	1280	<b>Control:</b>	ON/OFF
<b>Supply voltage [V]:</b>	230	<b>Dimensions (H/W/T/S) [mm]:</b>	fi=60 L=170
<b>Frequency [Hz]:</b>	50-60	<b>Mounting dimensions [mm]:</b>	L= 40mm fi6mm
<b>Luminous efficacy [lm/W]:</b>	90	<b>Ingress protection:</b>	IP20
<b>Electrical protection class:</b>	I	<b>Mounting version:</b>	surface
<b>Energy efficiency class:</b>	E	<b>Cable length [m]:</b>	1.50
<b>Beam angle [°]:</b>	20	<b>Dimensions of single box [mm]:</b>	fi=70mm L=200mm
<b>Colour rendering index:</b>	<80	<b>LED lifespan L90B10 [h]:</b>	60000
<b>Light colour:</b>	ciepla biel	<b>CE certificate:</b>	<a href="#">51/2025</a>
<b>Exchangeable source:</b>	yes	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Optics material:</b>	aluminium		
<b>Colour of the body:</b>	silver		

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 51/2025