LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 NT BLACK 830 DALI (12W)

DETAILED CARD





TECHNICAL PARAMETERS

779121
IP20
12
1280
3000
80
I
E
aluminium
black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

- Lungo II LED luminaire is used in spaces such as:
- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 NT BLACK 830 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

lu de co	770404	Colour of the heads	h la al-
Index:	779121	Colour of the body:	black
EAN:	5905963779121	Ring material:	aluminium
Light source:	LED	Ring colour:	black
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170
Supply voltage [V]:	230	Mounting dimensions [mm]:	L= 40mm fi6mm
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1280	Mounting version:	surface
Luminous efficacy [lm/W]:	90	DIMM DALI:	yes
Energy efficiency class:	E	Control:	yes
Electrical protection class:	1	Cable length [m]:	1.50
Colour temperature [K]:	3000	Number on the palette [pcs]:	1496
Colour rendering index:	80	Dimensions of single box [mm]:	fi=70mm L=200mm
Beam angle [°]:	20	Net weight [kg]:	0.500
Light colour:	ciepła biel	Gross weight [kg]:	0.600
Exchangeable source:	yes	LED lifespan L90B10 [h]:	60000
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	<u>51/2025</u>
Material of the body:	aluminium	Manual:	Download PDF

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 51/2025

X



Lena Lighting S.A. ul. Kórnicka 52, 63-000 Środa Wielkopolska tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl

This product is a subject to electric and electronic waste equipment regulations (WEEE).