

LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20 NT BLACK 830 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779145
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Colour rendering index:	<80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($R_a \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20 NT BLACK 830 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779145
Rated power of the luminaire [W]:	12
EAN:	5905963779145
Colour temperature [K]:	3000
Light source:	LED
Luminous flux [lm]:	1330
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	106
Electrical protection class:	I
Energy efficiency class:	E
Beam angle [°]:	70
Colour rendering index:	<80
Light colour:	ciepła biel
Exchangeable source:	yes
Optics material:	aluminium
Colour of the body:	black

Optics:	reflector
Material of the body:	aluminium
Ring colour:	black
Wire type:	czarny oplot
Ring material:	aluminium
Control:	yes
DIMM DALI:	yes
Dimensions (H/W/T/S) [mm]:	fi=60 L=170
Mounting dimensions [mm]:	L= 40mm fi6mm
Ingress protection:	IP20
Mounting version:	surface
Cable length [m]:	1.50
Dimensions of single box [mm]:	fi=70mm L=200mm
LED lifespan L90B10 [h]:	60000
CE certificate:	51/2025
Manual:	Download PDF