# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 NT BLACK 840 (12W)

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index:	779268
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1170
Colour temperature [K]:	4000
Colour rendering index:	<80
Electrical protection class:	1
Energy efficiency class:	Е
Material of the body:	aluminium
Colour of the body:	black

## **CHARACTERISTICS**

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra  $\geq$  80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

#### **APPLICATION**

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left$
- entrance areas and lobbies
- staircases
- reception areas



# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 NT BLACK 840 (12W)

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	779268
Rated power of the luminaire [W]:	12
EAN:	5905963779268
Colour temperature [K]:	4000
Light source:	LED
Luminous flux [Im]:	1170
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	95
Electrical protection class:	1
Energy efficiency class:	E
Beam angle [°]:	70
Colour rendering index:	<80
Light colour:	neutralna biel
Exchangeable source:	yes
Optics material:	aluminium
Colour of the body:	black

Optics:	reflector
Material of the body:	aluminium
Ring colour:	black
Wire type:	czarny oplot
Ring material:	aluminium
Control:	ON/OFF
Dimensions (H/W/T/S) [mm]:	fi=60 L=170
Mounting dimensions [mm]:	L= 40mm fi6mm
Ingress protection:	IP20
Mounting version:	surface
Cable length [m]:	1.50
Dimensions of single box [mm]:	fi=70mm L=200mm
LED lifespan L90B10 [h]:	60000
CE certificate:	<u>51/2025</u>
Manual:	Download PDF

Card creation date: 23 May 2025



