

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 NT WHITE 840 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779275
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1020
Colour temperature [K]:	4000
Colour rendering index:	<80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 NT WHITE 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779275
Rated power of the luminaire [W]:	12
EAN:	5905963779275
Colour temperature [K]:	4000
Light source:	LED
Luminous flux [lm]:	1020
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	85
Electrical protection class:	I
Energy efficiency class:	E
Beam angle [°]:	20
Colour rendering index:	<80
Light colour:	neutralna biel
Exchangeable source:	yes
Optics material:	aluminium
Colour of the body:	white

Optics:	reflector
Material of the body:	aluminium
Ring colour:	white
Wire type:	biały oplot
Ring material:	aluminium
Control:	ON/OFF
Dimensions (H/W/T/S) [mm]:	fi=60 L=170
Mounting dimensions [mm]:	L= 40mm fi6mm
Ingress protection:	IP20
Mounting version:	surface
Cable length [m]:	1.50
Dimensions of single box [mm]:	fi=70mm L=200mm
LED lifespan L90B10 [h]:	60000
CE certificate:	51/2025
Manual:	Download PDF

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl