LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 NT WHITE 840 (12W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:779282Ingress protection:IP20Rated power of the luminaire [W]*:12Luminous flux [Im]*:120Colour temperature [K]:4000Colour rendering index:80Electrical protection class:1Energy efficiency class:EMaterial of the body:auminumColour of the body:white		
Rated power of the luminaire [W]*:12Luminous flux [Im]*:1120Colour temperature [K]:4000Colour rendering index:80Electrical protection class:IEnergy efficiency class:EMaterial of the body:aluminium	Index:	779282
Luminous flux [Im]*:1120Colour temperature [K]:4000Colour rendering index:80Electrical protection class:IEnergy efficiency class:EMaterial of the body:aluminium	Ingress protection:	IP20
Colour temperature [K]:4000Colour rendering index:80Electrical protection class:IEnergy efficiency class:EMaterial of the body:aluminium	Rated power of the luminaire [W]*:	12
Colour rendering index:80Electrical protection class:IEnergy efficiency class:EMaterial of the body:aluminium	Luminous flux [lm]*:	1120
Electrical protection class:IEnergy efficiency class:EMaterial of the body:aluminium	Colour temperature [K]:	4000
Energy efficiency class: E Material of the body: aluminium	Colour rendering index:	80
Material of the body: aluminium	Electrical protection class:	I
	Energy efficiency class:	E
Colour of the body: white	Material of the body:	aluminium
	Colour of the body:	white

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

- Lungo II LED luminaire is used in spaces such as:
- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 NT WHITE 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779282	Colour of the heady	white
index:	779282	Colour of the body:	white
EAN:	5905963779282	Ring material:	aluminium
Light source:	LED	Ring colour:	white
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170
Supply voltage [V]:	230	Mounting dimensions [mm]:	L= 40mm fi6mm
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1120	Mounting version:	surface
Luminous efficacy [lm/W]:	91	Control:	ON/OFF
Energy efficiency class:	E	Cable length [m]:	1.50
Electrical protection class:	1	Number on the palette [pcs]:	1496
Colour temperature [K]:	4000	Dimensions of single box [mm]:	fi=70mm L=200mm
Colour rendering index:	80	Net weight [kg]:	0.500
Beam angle [°]:	40	Gross weight [kg]:	0.600
Light colour:	neutralna biel	LED lifespan L90B10 [h]:	60000
Exchangeable source:	yes	Warranty [years]:	5
Optics material:	aluminium	CE certificate:	<u>51/2025</u>
Optics:	reflector	Manual:	Download PDF
Material of the body:	aluminium		

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE).



A