

LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 NT SILVER 840 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|-----------|
| Index: | 779312 |
| Ingress protection: | IP20 |
| Rated power of the luminaire [W]*: | 12 |
| Luminous flux [lm]*: | 1120 |
| Colour temperature [K]: | 4000 |
| Color rendering index (Ra) >: | 80 |
| Electrical protection class: | I |
| Energy efficiency class: | E |
| Material of the body: | aluminium |
| Colour of the body: | silver |

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 NT SILVER 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|----------------|---------------------------------------|---|
| Index: | 779312 | Ring material: | aluminium |
| EAN: | 5905963779312 | Ring colour: | silver |
| Light source: | LED | Dimensions (H/W/T/S) [mm]: | fi=60 L=170 |
| Rated power of the luminaire [W]: | 12 | Mounting dimensions [mm]: | L= 40mm fi6mm |
| Supply voltage [V]: | 230 | Ingress protection: | IP20 |
| Frequency [Hz]: | 50-60 | Mounting version: | surface |
| Luminous flux [lm]: | 1120 | Control: | ON/OFF |
| Luminous efficacy [lm/W]: | 91 | Cable length [m]: | 1.50 |
| Energy efficiency class: | E | Number on the palette [pcs]: | 1496 |
| Electrical protection class: | I | Dimensions of single box [mm]: | fi=70mm L=200mm |
| Colour temperature [K]: | 4000 | Net weight [kg]: | 0.500 |
| Color rendering index (Ra) >: | 80 | Gross weight [kg]: | 0.600 |
| Beam angle [°]: | 40 | LED lifespan L90B10 [h]: | 60000 |
| Light colour: | neutralna biel | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Exchangeable source: | yes | Warranty [years]: | 5 |
| Optics material: | aluminium | CE certificate: | 51/2025 |
| Optics: | reflector | Manual: | Download PDF |
| Material of the body: | aluminium | Category of application: | office lighting |
| Colour of the body: | silver | Plik LDT: | Download |

Card creation date: 25 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 51/2025