LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 NT SILVER 840 (12W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	779329
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1170
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	silver

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

- Lungo II LED luminaire is used in spaces such as:
- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 NT SILVER 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779329	Colour of the body:	silver
EAN:	5905963779329	Ring material:	aluminium
Light source:	LED	Ring colour:	silver
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170
Supply voltage [V]:	230	Mounting dimensions [mm]:	L= 40mm fi6mm
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1170	Mounting version:	surface
Luminous efficacy [lm/W]:	95	Control:	ON/OFF
Energy efficiency class:	E	Cable length [m]:	1.50
Electrical protection class:	1	Number on the palette [pcs]:	1496
Colour temperature [K]:	4000	Dimensions of single box [mm]:	fi=70mm L=200mm
Colour rendering index:	80	Net weight [kg]:	0.500
Beam angle [°]:	70	Gross weight [kg]:	0.600
Light colour:	neutralna biel	LED lifespan L90B10 [h]:	60000
Exchangeable source:	yes	Warranty [years]:	5
Optics material:	aluminium	CE certificate:	<u>51/2025</u>
Optics:	reflector	Manual:	Download PDF
Material of the body:	aluminium		

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

A This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 51/2025