

# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 NT WHITE 840 DALI (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |           |
|------------------------------------|-----------|
| Index:                             | 779411    |
| Ingress protection:                | IP20      |
| Rated power of the luminaire [W]*: | 12        |
| Luminous flux [lm]*:               | 1170      |
| Colour temperature [K]:            | 4000      |
| Colour rendering index:            | <80       |
| Electrical protection class:       | I         |
| Energy efficiency class:           | E         |
| Material of the body:              | aluminium |
| Colour of the body:                | white     |

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ( $R_a \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 NT WHITE 840 DALI (12W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                |                                |                              |
|-----------------------------------|----------------|--------------------------------|------------------------------|
| Index:                            | 779411         | Material of the body:          | aluminium                    |
| EAN:                              | 5905963779411  | Colour of the body:            | white                        |
| Light source:                     | LED            | Ring material:                 | aluminium                    |
| Rated power of the luminaire [W]: | 12             | Ring colour:                   | white                        |
| Supply voltage [V]:               | 230            | Dimensions (H/W/T/S) [mm]:     | fi=60 L=170                  |
| Frequency [Hz]:                   | 50-60          | Mounting dimensions [mm]:      | L= 40mm fi6mm                |
| Luminous flux [lm]:               | 1170           | Ingress protection:            | IP20                         |
| Luminous efficacy [lm/W]:         | 95             | Mounting version:              | surface                      |
| Energy efficiency class:          | E              | DIMM DALI:                     | yes                          |
| Electrical protection class:      | I              | Control:                       | yes                          |
| Colour temperature [K]:           | 4000           | Wire type:                     | white braid                  |
| Colour rendering index:           | <80            | Cable length [m]:              | 1.50                         |
| Beam angle [°]:                   | 70             | Dimensions of single box [mm]: | fi=70mm L=200mm              |
| Light colour:                     | neutralna biel | LED lifespan L90B10 [h]:       | 60000                        |
| Exchangeable source:              | yes            | CE certificate:                | <a href="#">51/2025</a>      |
| Optics material:                  | aluminium      | Manual:                        | <a href="#">Download PDF</a> |
| Optics:                           | reflector      |                                |                              |