LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 NT BLACK AND GOLD 840 DALI (12W)

DETAILED CARD





TECHNICAL PARAMETERS

| Index: | 779459 |
|------------------------------------|-----------|
| Ingress protection: | IP20 |
| Rated power of the luminaire [W]*: | 12 |
| Luminous flux [lm]*: | 1020 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| Electrical protection class: | I |
| Energy efficiency class: | E |
| Material of the body: | aluminium |
| Colour of the body: | black |
| | |

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

- Lungo II LED luminaire is used in spaces such as:
- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 NT BLACK AND GOLD 840 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 779459 | Colour of the body: | black |
|-----------------------------------|----------------|--------------------------------|-----------------|
| EAN: | 5905963779459 | Ring material: | aluminium |
| Light source: | LED | Ring colour: | gold |
| Rated power of the luminaire [W]: | 12 | Dimensions (H/W/T/S) [mm]: | fi=60 L=170 |
| Supply voltage [V]: | 230 | Mounting dimensions [mm]: | L= 40mm fi6mm |
| Frequency [Hz]: | 50-60 | Ingress protection: | IP20 |
| Luminous flux [lm]: | 1020 | Mounting version: | surface |
| Luminous efficacy [lm/W]: | 85 | DIMM DALI: | yes |
| Energy efficiency class: | E | Control: | yes |
| Electrical protection class: | 1 | Cable length [m]: | 1.50 |
| Colour temperature [K]: | 4000 | Number on the palette [pcs]: | 1496 |
| Colour rendering index: | 80 | Dimensions of single box [mm]: | fi=70mm L=200mm |
| Beam angle [°]: | 20 | Net weight [kg]: | 0.500 |
| Light colour: | neutralna biel | Gross weight [kg]: | 0.600 |
| Exchangeable source: | yes | LED lifespan L90B10 [h]: | 60000 |
| Optics material: | aluminium | Warranty [years]: | 5 |
| Optics: | reflector | CE certificate: | <u>51/2025</u> |
| Material of the body: | aluminium | Manual: | Download PDF |

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 51/2025

A This product is a subject to electric and electronic waste equipment regulations (WEEE).

