

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20 SUSPENDED BLACK 830 (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	779497
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ( $Ra \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20

## SUSPENDED BLACK 830 (12W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

<b>Index:</b>	779497	<b>Ring material:</b>	aluminium
<b>EAN:</b>	5905963779497	<b>Ring colour:</b>	black
<b>Light source:</b>	LED	<b>Dimensions (H/W/T/S) [mm]:</b>	fi=60 L=170 H=1500
<b>Rated power of the luminaire [W]:</b>	12	<b>Mounting dimensions [mm]:</b>	L=36mm fi6mm
<b>Supply voltage [V]:</b>	230	<b>Ingress protection:</b>	IP20
<b>Frequency [Hz]:</b>	50-60	<b>Mounting version:</b>	suspended
<b>Luminous flux [lm]:</b>	1330	<b>Control:</b>	ON/OFF
<b>Luminous efficacy [lm/W]:</b>	108	<b>Wire type:</b>	black braid
<b>Energy efficiency class:</b>	E	<b>Cable length [m]:</b>	1.50
<b>Electrical protection class:</b>	I	<b>Number on the palette [pcs]:</b>	416
<b>Colour temperature [K]:</b>	3000	<b>Dimensions of single box [mm]:</b>	fi=90mm L=335mm
<b>Colour rendering index:</b>	80	<b>Net weight [kg]:</b>	0.700
<b>Beam angle [°]:</b>	40	<b>Gross weight [kg]:</b>	0.900
<b>Light colour:</b>	ciepla biel	<b>LED lifespan L90B10 [h]:</b>	60000
<b>Exchangeable source:</b>	yes	<b>Warranty [years]:</b>	5
<b>Optics material:</b>	aluminium	<b>CE certificate:</b>	<a href="#">51/2025</a>
<b>Optics:</b>	reflector	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Material of the body:</b>	aluminium	<b>Category of application:</b>	office lighting
<b>Colour of the body:</b>	black	<b>Plik LDT:</b>	<a href="#">Download</a>

Card creation date: 25 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 51/2025