

# LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20 SUSPENDED BLACK AND GOLD 830 (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	779596
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ( $Ra \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20

## SUSPENDED BLACK AND GOLD 830 (12W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

<b>Index:</b>	779596	<b>Ring colour:</b>	gold
<b>EAN:</b>	5905963779596	<b>Dimensions (H/W/T/S) [mm]:</b>	fi=60 L=170 H=1500
<b>Light source:</b>	LED	<b>Mounting dimensions [mm]:</b>	L=36mm fi6mm
<b>Rated power of the luminaire [W]:</b>	12	<b>Ingress protection:</b>	IP20
<b>Supply voltage [V]:</b>	230	<b>Mounting version:</b>	suspended
<b>Frequency [Hz]:</b>	50-60	<b>Control:</b>	ON/OFF
<b>Luminous flux [lm]:</b>	1330	<b>Wire type:</b>	red braid
<b>Luminous efficacy [lm/W]:</b>	106	<b>Cable length [m]:</b>	1.50
<b>Energy efficiency class:</b>	E	<b>Number on the palette [pcs]:</b>	416
<b>Electrical protection class:</b>	I	<b>Dimensions of single box [mm]:</b>	fi=90mm L=335mm
<b>Colour temperature [K]:</b>	3000	<b>Net weight [kg]:</b>	0.700
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Gross weight [kg]:</b>	0.900
<b>Beam angle [°]:</b>	70	<b>LED lifespan L90B10 [h]:</b>	60000
<b>Light colour:</b>	ciepla biel	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Exchangeable source:</b>	yes	<b>Warranty [years]:</b>	5
<b>Optics material:</b>	aluminium	<b>CE certificate:</b>	<a href="#">51/2025</a>
<b>Optics:</b>	reflector	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Material of the body:</b>	aluminium	<b>Category of application:</b>	office lighting
<b>Colour of the body:</b>	black	<b>Plik LDT:</b>	<a href="#">Download</a>
<b>Ring material:</b>	aluminium		

Card creation date: 25 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 51/2025