

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

## SUSPENDED WHITE 830 DALI (12W)

DETAILED CARD



### TECHNICAL PARAMETERS

Index:	779633
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

### CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ( $R_a \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

### APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

## SUSPENDED WHITE 830 DALI (12W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	779633
EAN:	5905963779633
Light source:	LED
Rated power of the luminaire [W]:	12
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous flux [lm]:	1280
Luminous efficacy [lm/W]:	90
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	3000
Colour rendering index:	80
Beam angle [°]:	20
Light colour:	ciepła biel
Exchangeable source:	yes
Optics material:	aluminium
Optics:	reflector
Material of the body:	aluminium
Colour of the body:	white

Ring material:	aluminium
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	L=40mm fi6mm
Ingress protection:	IP20
Mounting version:	suspended
DIMM DALI:	yes
Control:	yes
Wire type:	white braid
Cable length [m]:	1.50
Number on the palette [pcs]:	416
Dimensions of single box [mm]:	fi=90mm L=400mm
Net weight [kg]:	0.700
Gross weight [kg]:	0.900
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	<a href="#">51/2025</a>
Manual:	<a href="#">Download PDF</a>

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)