

LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20 SUSPENDED BLACK AND GOLD 830 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779701
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($R_a \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20

SUSPENDED BLACK AND GOLD 830 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779701
EAN:	5905963779701
Light source:	LED
Rated power of the luminaire [W]:	12
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous flux [lm]:	1330
Luminous efficacy [lm/W]:	108
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	3000
Colour rendering index:	80
Beam angle [°]:	40
Light colour:	ciepła biel
Exchangeable source:	yes
Optics material:	aluminium
Optics:	reflector
Material of the body:	aluminium
Colour of the body:	black

Ring material:	aluminium
Ring colour:	gold
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	L=40mm fi6mm
Ingress protection:	IP20
Mounting version:	suspended
DIMM DALI:	yes
Control:	yes
Wire type:	red braid
Cable length [m]:	1.50
Number on the palette [pcs]:	416
Dimensions of single box [mm]:	fi=90mm L=400mm
Net weight [kg]:	0.700
Gross weight [kg]:	0.900
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	51/2025
Manual:	Download PDF