

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20

SUSPENDED BLACK 840 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779725
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1020
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($R_a \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20

SUSPENDED BLACK 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779725	Colour of the body:	black
EAN:	5905963779725	Ring material:	aluminium
Light source:	LED	Ring colour:	black
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Supply voltage [V]:	230	Mounting dimensions [mm]:	L=36mm fi6mm
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1020	Mounting version:	suspended
Luminous efficacy [lm/W]:	85	Control:	ON/OFF
Energy efficiency class:	E	Wire type:	black braid
Electrical protection class:	I	Cable length [m]:	1.50
Colour temperature [K]:	4000	Number on the palette [pcs]:	416
Colour rendering index:	80	Dimensions of single box [mm]:	fi=90mm L=335mm
Beam angle [°]:	20	Net weight [kg]:	0.700
Light colour:	neutralna biel	Gross weight [kg]:	0.900
Exchangeable source:	yes	LED lifespan L90B10 [h]:	60000
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	51/2025
Material of the body:	aluminium	Manual:	Download PDF

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl