## LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED WHITE 840 (12W)

**DETAILED CARD** 





#### **TECHNICAL PARAMETERS**

Index:	779763
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1120
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	1
Energy efficiency class:	Е
Material of the body:	aluminium
Colour of the body:	white



### **CHARACTERISTICS**

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra  $\geq$  80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

#### **APPLICATION**

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left$
- entrance areas and lobbies
- staircases
- reception areas



# LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED WHITE 840 (12W)

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	779763
EAN:	5905963779763
Light source:	LED
Rated power of the luminaire [W]:	12
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous flux [Im]:	1120
Luminous efficacy [lm/W]:	91
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	4000
Colour rendering index:	80
Beam angle [°]:	40
Light colour:	neutralna biel
Exchangeable source:	yes
Optics material:	aluminium
Optics:	reflector
Material of the body:	aluminium

Colour of the body:	white
Ring material:	aluminium
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	L=36mm fi6mm
Ingress protection:	IP20
Mounting version:	suspended
Control:	ON/OFF
Wire type:	white braid
Cable length [m]:	1.50
Number on the palette [pcs]:	416
Dimensions of single box [mm]:	fi=90mm L=335mm
Net weight [kg]:	0.700
Gross weight [kg]:	0.900
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	<u>51/2025</u>
Manual:	Download PDF

Card creation date: 23 May 2025



