

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED WHITE 840 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779770
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1170
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED WHITE 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779770	Colour of the body:	white
EAN:	5905963779770	Ring material:	aluminium
Light source:	LED	Ring colour:	white
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Supply voltage [V]:	230	Mounting dimensions [mm]:	L=36mm fi6mm
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1170	Mounting version:	suspended
Luminous efficacy [lm/W]:	95	Control:	ON/OFF
Energy efficiency class:	E	Wire type:	white braid
Electrical protection class:	I	Cable length [m]:	1.50
Colour temperature [K]:	4000	Number on the palette [pcs]:	416
Colour rendering index:	80	Dimensions of single box [mm]:	fi=90mm L=335mm
Beam angle [°]:	70	Net weight [kg]:	0.700
Light colour:	neutralna biel	Gross weight [kg]:	0.900
Exchangeable source:	yes	LED lifespan L90B10 [h]:	60000
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	51/2025
Material of the body:	aluminium	Manual:	Download PDF