

LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED SILVER 840 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779794
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1120
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	silver

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED SILVER 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779794	Ring colour:	silver
EAN:	5905963779794	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Light source:	LED	Mounting dimensions [mm]:	L=36mm fi6mm
Rated power of the luminaire [W]:	12	Ingress protection:	IP20
Supply voltage [V]:	230	Mounting version:	suspended
Frequency [Hz]:	50-60	Control:	ON/OFF
Luminous flux [lm]:	1120	Wire type:	black braid
Luminous efficacy [lm/W]:	91	Cable length [m]:	1.50
Energy efficiency class:	E	Number on the palette [pcs]:	416
Electrical protection class:	I	Dimensions of single box [mm]:	fi=90mm L=335mm
Colour temperature [K]:	4000	Net weight [kg]:	0.700
Color rendering index (Ra) >:	80	Gross weight [kg]:	0.900
Beam angle [°]:	40	LED lifespan L90B10 [h]:	60000
Light colour:	neutralna biel	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Exchangeable source:	yes	Warranty [years]:	5
Optics material:	aluminium	CE certificate:	51/2025
Optics:	reflector	Manual:	Download PDF
Material of the body:	aluminium	Category of application:	office lighting
Colour of the body:	silver	Plik LDT:	Download
Ring material:	aluminium		

Card creation date: 25 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025