LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 SUSPENDED BLACK AND GOLD 840 (12W)

DETAILED CARD





TECHNICAL PARAMETERS

| Index: | 779817 |
|------------------------------------|-----------|
| Ingress protection: | IP20 |
| Rated power of the luminaire [W]*: | 12 |
| Luminous flux [lm]*: | 1020 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| Electrical protection class: | 1 |
| Energy efficiency class: | Е |
| Material of the body: | aluminium |
| Colour of the body: | black |

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20 SUSPENDED BLACK AND GOLD 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 779817 |
|-----------------------------------|----------------|
| EAN: | 5905963779817 |
| Light source: | LED |
| Rated power of the luminaire [W]: | 12 |
| Supply voltage [V]: | 230 |
| Frequency [Hz]: | 50-60 |
| Luminous flux [Im]: | 1020 |
| Luminous efficacy [lm/W]: | 85 |
| Energy efficiency class: | E |
| Electrical protection class: | 1 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| Beam angle [°]: | 20 |
| Light colour: | neutralna biel |
| Exchangeable source: | yes |
| Optics material: | aluminium |
| Optics: | reflector |
| Material of the body: | aluminium |

| Colour of the body: | black |
|--------------------------------|--------------------|
| Ring material: | aluminium |
| Ring colour: | gold |
| Dimensions (H/W/T/S) [mm]: | fi=60 L=170 H=1500 |
| Mounting dimensions [mm]: | L=36mm fi6mm |
| Ingress protection: | IP20 |
| Mounting version: | suspended |
| Control: | ON/OFF |
| Wire type: | red braid |
| Cable length [m]: | 1.50 |
| Number on the palette [pcs]: | 416 |
| Dimensions of single box [mm]: | fi=90mm L=335mm |
| Net weight [kg]: | 0.700 |
| Gross weight [kg]: | 0.900 |
| LED lifespan L90B10 [h]: | 60000 |
| Warranty [years]: | 5 |
| CE certificate: | <u>51/2025</u> |
| Manual: | Download PDF |

Card creation date: 23 May 2025



