LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED BLACK AND GOLD 840 (12W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	779824	
Ingress protection:	IP20	
Rated power of the luminaire [W]*:	12	
Luminous flux [lm]*:	1120	
Colour temperature [K]:	4000	
Colour rendering index:	80	
Electrical protection class:	ctrical protection class:	
Energy efficiency class:	E	
Material of the body:	aluminium	
Colour of the body:	black	

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

- Lungo II LED luminaire is used in spaces such as:
- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



LUNGO II 1120LM 40ST FI60 H170MM I CL. IP20 SUSPENDED BLACK AND GOLD 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

	770004		
Index:	779824	Colour of the body:	black
EAN:	5905963779824	Ring material:	aluminium
Light source:	LED	Ring colour:	gold
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Supply voltage [V]:	230	Mounting dimensions [mm]:	L=36mm fi6mm
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1120	Mounting version:	suspended
Luminous efficacy [lm/W]:	91	Control:	ON/OFF
Energy efficiency class:	E	Wire type:	red braid
Electrical protection class:	1	Cable length [m]:	1.50
Colour temperature [K]:	4000	Number on the palette [pcs]:	416
Colour rendering index:	80	Dimensions of single box [mm]:	fi=90mm L=335mm
Beam angle [°]:	40	Net weight [kg]:	0.700
Light colour:	neutralna biel	Gross weight [kg]:	0.900
Exchangeable source:	yes	LED lifespan L90B10 [h]:	60000
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	<u>51/2025</u>
Material of the body:	aluminium	Manual:	Download PDF

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 51/2025

This product is a subject to electric and electronic waste equipment regulations (WEEE).



Lena Lighting S.A. ul. Kórnicka 52, 63-000 Środa Wielkopolska tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl