

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED WHITE 840 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	779893
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1170
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED WHITE 840 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	779893	Ring colour:	white
EAN:	5905963779893	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Light source:	LED	Mounting dimensions [mm]:	L=40mm fi6mm
Rated power of the luminaire [W]:	12	Ingress protection:	IP20
Supply voltage [V]:	230	Mounting version:	suspended
Frequency [Hz]:	50-60	DIMM DALI:	yes
Luminous flux [lm]:	1170	Control:	yes
Luminous efficacy [lm/W]:	95	Wire type:	white braid
Energy efficiency class:	E	Cable length [m]:	1.50
Electrical protection class:	I	Number on the palette [pcs]:	416
Colour temperature [K]:	4000	Dimensions of single box [mm]:	fi=90mm L=400mm
Color rendering index (Ra) >:	80	Net weight [kg]:	0.700
Beam angle [°]:	70	Gross weight [kg]:	0.900
Light colour:	neutralna biel	LED lifespan L90B10 [h]:	60000
Exchangeable source:	yes	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	51/2025
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	white	Category of application:	office lighting
Ring material:	aluminium	Plik LDT:	Download

Card creation date: 25 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025