

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

## SUSPENDED TRACK BLACK 830 (12W)

DETAILED CARD



### TECHNICAL PARAMETERS

Index:	779961
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

### CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ( $Ra \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

### APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

## SUSPENDED TRACK BLACK 830 (12W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	779961	Colour of the body:	black
EAN:	5905963779961	Ring material:	aluminium
Light source:	LED	Ring colour:	black
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Supply voltage [V]:	230	Mounting dimensions [mm]:	szynoprzewód
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1280	Mounting version:	suspended from trunking
Luminous efficacy [lm/W]:	90	Control:	ON/OFF
Energy efficiency class:	E	Wire type:	black braid
Electrical protection class:	II	Cable length [m]:	1.50
Colour temperature [K]:	3000	Number on the palette [pcs]:	416
Colour rendering index:	80	Dimensions of single box [mm]:	fi=90mm L=335mm
Beam angle [°]:	20	Net weight [kg]:	0.600
Light colour:	ciepła biel	Gross weight [kg]:	0.700
Exchangeable source:	yes	LED lifespan L90B10 [h]:	60000
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	<a href="#">51/2025</a>
Material of the body:	aluminium	Manual:	<a href="#">Download PDF</a>