LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK 830 (12W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	779961
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Colour rendering index:	<80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK 830 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]: EAN: 5905963779961 Colour temperature [K]: 3000 Light source: LED Luminous flux [Im]: 1280 Supply voltage [V]: 230 Frequency [Hz]: 50-60 Luminous efficacy [Im/W]: 90 Electrical protection class: II Energy efficiency class: E Beam angle [°]: 20 Colour rendering index: <80 Light colour: ciepła biel Exchangeable source: yes Optics material: aluminium Colour of the body: black	Index:	779961
Colour temperature [K]: Light source: Luminous flux [Im]: Supply voltage [V]: Frequency [Hz]: Luminous efficacy [Im/W]: Electrical protection class: Energy efficiency class: Beam angle [°]: Colour rendering index: Light colour: Exchangeable source: Optics material: S000 LED 1280 230 Frequency [Hz]: 50-60 90 II Electrical protection class: E 80 Ciepła biel Exchangeable source: yes Optics material:	Rated power of the luminaire [W]:	12
Light source: Luminous flux [lm]: Supply voltage [V]: Frequency [Hz]: Luminous efficacy [lm/W]: Electrical protection class: Energy efficiency class: Beam angle [°]: Colour rendering index: Light colour: Exchangeable source: Optics material:	EAN:	5905963779961
Luminous flux [Im]: Supply voltage [V]: Frequency [Hz]: Luminous efficacy [Im/W]: Electrical protection class: Energy efficiency class: Beam angle [°]: Colour rendering index: Light colour: Exchangeable source: Optics material:	Colour temperature [K]:	3000
Supply voltage [V]: Frequency [Hz]: 50-60 Luminous efficacy [Im/W]: Electrical protection class: Energy efficiency class: Beam angle [°]: Colour rendering index: Light colour: Exchangeable source: Optics material: 230 90 11 220 20 Colour rendering index: <a href="mailto:sep-la</th><th>Light source:</th><th>LED</th></tr><tr><th>Frequency [Hz]: 50-60 Luminous efficacy [Im/W]: 90 Electrical protection class: II Energy efficiency class: E Beam angle [°]: 20 Colour rendering index: <80 Light colour: ciepła biel Exchangeable source: yes Optics material: aluminium</th><th>Luminous flux [Im]:</th><th>1280</th></tr><tr><th>Luminous efficacy [lm/W]: Electrical protection class: Energy efficiency class: Beam angle [°]: Colour rendering index: Light colour: Exchangeable source: Optics material: 90 20 20 20 20 480 ciepła biel Exchangeable source: yes aluminium</th><th>Supply voltage [V]:</th><th>230</th></tr><tr><th>Electrical protection class: Energy efficiency class: Beam angle [°]: Colour rendering index: Light colour: Exchangeable source: Optics material: II E E Colour class: E Beam angle [°]: 20 Ciepła biel yes aluminium</th><th>Frequency [Hz]:</th><th>50-60</th></tr><tr><th>Energy efficiency class: Beam angle [°]: Colour rendering index: Light colour: Exchangeable source: Optics material: Energy efficiency class: E 20 	Luminous efficacy [lm/W]:	90
Beam angle [°]: 20 Colour rendering index: <80 Light colour: ciepła biel Exchangeable source: yes Optics material: aluminium	Electrical protection class:	II
Colour rendering index: <80 Light colour: ciepła biel Exchangeable source: yes Optics material: aluminium	Energy efficiency class:	E
Light colour: ciepła biel Exchangeable source: yes Optics material: aluminium	Beam angle [°]:	20
Exchangeable source: yes Optics material: aluminium	Colour rendering index:	<80
Optics material: aluminium	Light colour:	ciepła biel
	Exchangeable source:	yes
Colour of the body: black	Optics material:	aluminium
	Colour of the body:	black

Optics:	reflector
Material of the body:	aluminium
Ring colour:	black
Wire type:	czarny oplot
Ring material:	aluminium
Control:	ON/OFF
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	szynoprzewód
Ingress protection:	IP20
Mounting version:	suspended from trunking
Cable length [m]:	1.50
Dimensions of single box [mm]:	fi=90mm L=335mm
LED lifespan L90B10 [h]:	60000
CE certificate:	<u>51/2025</u>
Manual:	Download PDF

Card creation date: 23 May 2025



