

LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20

SUSPENDED TRACK WHITE 830 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780011
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20

SUSPENDED TRACK WHITE 830 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780011	Ring material:	aluminium
EAN:	5905963780011	Ring colour:	white
Light source:	LED	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Rated power of the luminaire [W]:	12	Mounting dimensions [mm]:	szynoprzewód
Supply voltage [V]:	230	Ingress protection:	IP20
Frequency [Hz]:	50-60	Mounting version:	suspended from trunking
Luminous flux [lm]:	1330	Control:	ON/OFF
Luminous efficacy [lm/W]:	106	Wire type:	white braid
Energy efficiency class:	E	Cable length [m]:	1.50
Electrical protection class:	II	Number on the palette [pcs]:	416
Colour temperature [K]:	3000	Dimensions of single box [mm]:	fi=90mm L=335mm
Colour rendering index:	80	Net weight [kg]:	0.600
Beam angle [°]:	70	Gross weight [kg]:	0.700
Light colour:	ciepla biel	LED lifespan L90B10 [h]:	60000
Exchangeable source:	yes	Warranty [years]:	5
Optics material:	aluminium	CE certificate:	51/2025
Optics:	reflector	Manual:	Download PDF
Material of the body:	aluminium	Category of application:	office lighting
Colour of the body:	white	Plik LDT:	Download

Card creation date: 25 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 51/2025