

LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 SUSPENDED TRACK SILVER 830 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780028
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	20
Material of the body:	aluminium
Colour of the body:	silver
Ring colour:	silver
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index (Ra \geq 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20 SUSPENDED TRACK SILVER 830 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780028	Colour of the body:	silver
EAN:	5905963780028	Ring material:	aluminium
Category type:	decorative fixtures	Ring colour:	silver
Category of application:	architectural, office lighting, commercial facilities	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Light source:	LED	Mounting dimensions [mm]:	szynoprzewód
Rated power of the luminaire [W]:	12	Ingress protection:	IP20
Luminous flux [lm]:	1280	Mounting version:	suspended from trunking
Supply voltage [V]:	230	Dimensions of single box [mm]:	fi=90mm L=335mm
Frequency [Hz]:	50-60	Number on the palette [pcs]:	416
Luminous efficacy [lm/W]:	90	Net weight [kg]:	0.600
Energy efficiency class:	E	Gross weight [kg]:	0.700
Electrical protection class:	II	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour temperature [K]:	3000	Warranty [years]:	5
Color rendering index (Ra) >:	80	CE certificate:	01/2026
LED lifespan L90B10 [h]:	60000	Manual:	Download PDF
Beam angle [°]:	20	Nominal power [W]:	13
Exchangeable source:	yes	Control:	ON/OFF
Optics:	reflector	Wire type:	black braid
Optics material:	aluminium	Cable length [m]:	1.50
Material of the body:	aluminium	Plik LDT:	Download

Card creation date: 21 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 01/2026