

LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

SUSPENDED TRACK BLACK AND GOLD 830 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780059
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Colour rendering index:	<80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ($R_a \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

SUSPENDED TRACK BLACK AND GOLD 830 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780059	Optics:	reflector
EAN:	5905963780059	Material of the body:	aluminium
Light source:	LED	Colour of the body:	black
Rated power of the luminaire [W]:	12	Ring material:	aluminium
Supply voltage [V]:	230	Ring colour:	gold
Frequency [Hz]:	50-60	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Luminous flux [lm]:	1280	Mounting dimensions [mm]:	szynoprzewód
Luminous efficacy [lm/W]:	90	Ingress protection:	IP20
Energy efficiency class:	E	Mounting version:	suspended from trunking
Electrical protection class:	II	Control:	ON/OFF
Colour temperature [K]:	3000	Wire type:	red braid
Colour rendering index:	<80	Cable length [m]:	1.50
Beam angle [°]:	20	Dimensions of single box [mm]:	fi=90mm L=335mm
Light colour:	ciepła biel	LED lifespan L90B10 [h]:	60000
Exchangeable source:	yes	CE certificate:	51/2025
Optics material:	aluminium	Manual:	Download PDF