

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK AND GOLD 830 (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	780066
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	40
Material of the body:	aluminium
Colour of the body:	black
Ring colour:	gold
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra ≥ 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20

## SUSPENDED TRACK BLACK AND GOLD 830 (12W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

<b>Index:</b>	780066	<b>Colour of the body:</b>	black
<b>EAN:</b>	5905963780066	<b>Ring material:</b>	aluminium
<b>Category type:</b>	decorative fixtures	<b>Ring colour:</b>	gold
<b>Category of application:</b>	architectural, office lighting, commercial facilities	<b>Dimensions (H/W/T/S) [mm]:</b>	fi=60 L=170 H=1500
<b>Light source:</b>	LED	<b>Mounting dimensions [mm]:</b>	szynoprzewód
<b>Rated power of the luminaire [W]:</b>	12	<b>Ingress protection:</b>	IP20
<b>Luminous flux [lm]:</b>	1330	<b>Mounting version:</b>	suspended from trunking
<b>Supply voltage [V]:</b>	230	<b>Dimensions of single box [mm]:</b>	fi=90mm L=335mm
<b>Frequency [Hz]:</b>	50-60	<b>Number on the palette [pcs]:</b>	416
<b>Luminous efficacy [lm/W]:</b>	108	<b>Net weight [kg]:</b>	0.600
<b>Energy efficiency class:</b>	E	<b>Gross weight [kg]:</b>	0.700
<b>Electrical protection class:</b>	II	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Colour temperature [K]:</b>	3000	<b>Warranty [years]:</b>	5
<b>Color rendering index (Ra) &gt;:</b>	80	<b>CE certificate:</b>	<a href="#">01/2026</a>
<b>LED lifespan L90B10 [h]:</b>	60000	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Beam angle [°]:</b>	40	<b>Nominal power [W]:</b>	13
<b>Exchangeable source:</b>	yes	<b>Control:</b>	ON/OFF
<b>Optics:</b>	reflector	<b>Wire type:</b>	red braid
<b>Optics material:</b>	aluminium	<b>Cable length [m]:</b>	1.50
<b>Material of the body:</b>	aluminium	<b>Plik LDT:</b>	<a href="#">Download</a>

Card creation date: 21 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 01/2026