

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK AND GOLD 830 (12W)

## DETAILED CARD



## TECHNICAL PARAMETERS

Index:	780066
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	40
Material of the body:	aluminium
Colour of the body:	black
Ring colour:	gold
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500

## CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index (Ra  $\geq$  80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

## APPLICATION

Luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK BLACK AND GOLD 830 (12W)

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	780066	Colour of the body:	black
EAN:	5905963780066	Ring material:	aluminium
Category type:	decorative fixtures	Ring colour:	gold
Category of application:	architectural, office lighting, commercial facilities	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Light source:	LED	Mounting dimensions [mm]:	szynoprzewód
Rated power of the luminaire [W]:	12	Ingress protection:	IP20
Luminous flux [lm]:	1330	Mounting version:	suspended from trunking
Supply voltage [V]:	230	Dimensions of single box [mm]:	fi=90mm L=335mm
Frequency [Hz]:	50-60	Number on the palette [pcs]:	416
Luminous efficacy [lm/W]:	108	Net weight [kg]:	0.600
Energy efficiency class:	E	Gross weight [kg]:	0.700
Electrical protection class:	II	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour temperature [K]:	3000	Warranty [years]:	5
Color rendering index (Ra) >:	80	CE certificate:	<a href="#">01/2026</a>
LED lifespan L90B10 [h]:	60000	Manual:	<a href="#">Download PDF</a>
Beam angle [°]:	40	Nominal power [W]:	13
Exchangeable source:	yes	Control:	ON/OFF
Optics:	reflector	Wire type:	red braid
Optics material:	aluminium	Cable length [m]:	1.50
Material of the body:	aluminium	Plik LDT:	<a href="#">Download</a>

Card creation date: 21 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 01/2026