

LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20

SUSPENDED TRACK BLACK AND GOLD 830 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780073
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ($Ra \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1330LM 70ST FI60 H170MM I CL. IP20

SUSPENDED TRACK BLACK AND GOLD 830 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780073	Colour of the body:	black
EAN:	5905963780073	Ring material:	aluminium
Light source:	LED	Ring colour:	gold
Rated power of the luminaire [W]:	12	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Supply voltage [V]:	230	Mounting dimensions [mm]:	szynoprzewód
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	1330	Mounting version:	suspended from trunking
Luminous efficacy [lm/W]:	106	Control:	ON/OFF
Energy efficiency class:	E	Wire type:	red braid
Electrical protection class:	II	Cable length [m]:	1.50
Colour temperature [K]:	3000	Number on the palette [pcs]:	416
Colour rendering index:	80	Dimensions of single box [mm]:	fi=90mm L=335mm
Beam angle [°]:	70	Net weight [kg]:	0.600
Light colour:	ciepła biel	Gross weight [kg]:	0.700
Exchangeable source:	yes	LED lifespan L90B10 [h]:	60000
Optics material:	aluminium	Warranty [years]:	5
Optics:	reflector	CE certificate:	51/2025
Material of the body:	aluminium	Manual:	Download PDF