

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

## SUSPENDED TRACK WHITE 830 DALI (12W)

DETAILED CARD



### TECHNICAL PARAMETERS

Index:	780110
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1280
Colour temperature [K]:	3000
Colour rendering index:	<80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

### CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ( $R_a \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

### APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1280LM 20ST FI60 H170MM I CL. IP20

## SUSPENDED TRACK WHITE 830 DALI (12W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	780110
Rated power of the luminaire [W]:	12
EAN:	5905963780110
Colour temperature [K]:	3000
Light source:	LED
Luminous flux [lm]:	1280
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	90
Electrical protection class:	II
Energy efficiency class:	E
Beam angle [°]:	20
Colour rendering index:	<80
Light colour:	ciepła biel
Exchangeable source:	yes
Optics material:	aluminium
Colour of the body:	white

Optics:	reflector
Material of the body:	aluminium
Ring colour:	white
Wire type:	biały oplot
Ring material:	aluminium
Control:	yes
DIMM DALI:	yes
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	szynoprzewód
Ingress protection:	IP20
Mounting version:	suspended from trunking
Cable length [m]:	1.50
Dimensions of single box [mm]:	fi=90mm L=400mm
LED lifespan L90B10 [h]:	60000
CE certificate:	<a href="#">51/2025</a>
Manual:	<a href="#">Download PDF</a>

Card creation date: 23 May 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025