

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20

## SUSPENDED TRACK WHITE 830 DALI (12W)

DETAILED CARD



### TECHNICAL PARAMETERS

Index:	780127
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

### CHARACTERISTICS

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index ( $R_a \geq 80$ )- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

### APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

# LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20

## SUSPENDED TRACK WHITE 830 DALI (12W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	780127
EAN:	5905963780127
Light source:	LED
Rated power of the luminaire [W]:	12
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous flux [lm]:	1330
Luminous efficacy [lm/W]:	108
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000
Colour rendering index:	80
Beam angle [°]:	40
Light colour:	ciepła biel
Exchangeable source:	yes
Optics material:	aluminium
Optics:	reflector
Material of the body:	aluminium
Colour of the body:	white

Ring material:	aluminium
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	szynoprzewód
Ingress protection:	IP20
Mounting version:	suspended from trunking
DIMM DALI:	yes
Control:	yes
Wire type:	white braid
Cable length [m]:	1.50
Number on the palette [pcs]:	312
Dimensions of single box [mm]:	fi=90mm L=400mm
Net weight [kg]:	0.600
Gross weight [kg]:	0.700
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	<a href="#">51/2025</a>
Manual:	<a href="#">Download PDF</a>