LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK SILVER 830 DALI (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780158
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1330
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	40
Material of the body:	aluminium
Colour of the body:	silver
Ring colour:	silver
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra ≥ 80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Luminaire is used in spaces such as:
- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1330LM 40ST FI60 H170MM I CL. IP20 SUSPENDED TRACK SILVER 830 DALI (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780158
EAN:	5905963780158
Category type:	decorative fixtures
Category of application:	architectural, office lighting, commercial facilities
Light source:	LED
Rated power of the luminaire [W]:	12
Luminous flux [lm]:	1330
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	108
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
LED lifespan L90B10 [h]:	60000
Working temperature [°C]:	from 0 to +35
Beam angle [°]:	40
Exchangeable source:	yes
Optics:	reflector
Optics material:	aluminium
Material of the body:	aluminium

Colour of the body:	silver
Ring material:	aluminium
Ring colour:	silver
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	szynoprzewód
Ingress protection:	IP20
Mounting version:	suspended from trunking
Control:	yes
DIMM DALI:	yes
Dimensions of single box [mm]:	fi=90mm L=400mm
Number on the palette [pcs]:	312
Net weight [kg]:	0.600
Gross weight [kg]:	0.700
Wire type:	black braid
Cable length [m]:	1.50
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	01/2026
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

Card creation date: 21 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 01/2026

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl