

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20

SUSPENDED TRACK WHITE 840 (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	780233
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1020
Colour temperature [K]:	4000
Colour rendering index:	<80
Electrical protection class:	II
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

Lungo II LED is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:-** High light quality and high colour rendering index ($R_a \geq 80$)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

APPLICATION

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas

LUNGO II 1020LM 20ST FI60 H170MM I CL. IP20

SUSPENDED TRACK WHITE 840 (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	780233	Optics:	reflector
EAN:	5905963780233	Material of the body:	aluminium
Light source:	LED	Colour of the body:	white
Rated power of the luminaire [W]:	12	Ring material:	aluminium
Supply voltage [V]:	230	Ring colour:	white
Frequency [Hz]:	50-60	Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Luminous flux [lm]:	1020	Mounting dimensions [mm]:	szynoprzewód
Luminous efficacy [lm/W]:	85	Ingress protection:	IP20
Energy efficiency class:	E	Mounting version:	suspended from trunking
Electrical protection class:	II	Control:	ON/OFF
Colour temperature [K]:	4000	Wire type:	white braid
Colour rendering index:	<80	Cable length [m]:	1.50
Beam angle [°]:	20	Dimensions of single box [mm]:	fi=90mm L=335mm
Light colour:	neutralna biel	LED lifespan L90B10 [h]:	60000
Exchangeable source:	yes	CE certificate:	51/2025
Optics material:	aluminium	Manual:	Download PDF

Card creation date: 23 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 51/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl