# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 (12W)

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index:	780257
Ingress protection:	IP20
Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1170
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	II
Energy efficiency class:	Е
Material of the body:	aluminium
Colour of the body:	white

## **CHARACTERISTICS**

**Lungo II LED** is a modern luminaire by the company, designed for functional and aesthetic lighting of commercial interiors, offices and traffic zones in public buildings. With its slim, geometric form and high quality workmanship, it fits perfectly into modern architectural spaces. **Advantages of the Lungo II LED luminaire:**- High light quality and high colour rendering index (Ra  $\geq$  80)- Modern, minimalist design suitable for offices, corridors, receptions and entrance areas- Can be surface-mounted or suspended

# **APPLICATION**

Lungo II LED luminaire is used in spaces such as:

- corridors and passageways in office and institutional buildings
- entrance areas and lobbies
- staircases
- reception areas



# LUNGO II 1170LM 70ST FI60 H170MM I CL. IP20 SUSPENDED TRACK WHITE 840 (12W)

**DETAILED CARD** 

## **TECHNICAL PARAMETERS TABLE**

Index:	780257
EAN:	5905963780257
Light source:	LED
Rated power of the luminaire [W]:	12
Supply voltage [V]:	230
Frequency [Hz]:	50-60
Luminous flux [Im]:	1170
Luminous efficacy [lm/W]:	95
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	80
Beam angle [°]:	70
Light colour:	neutralna biel
Exchangeable source:	yes
Optics material:	aluminium
Optics:	reflector
Material of the body:	aluminium

Colour of the body:	white
Ring material:	aluminium
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	fi=60 L=170 H=1500
Mounting dimensions [mm]:	szynoprzewód
Ingress protection:	IP20
Mounting version:	suspended from trunking
Control:	ON/OFF
Wire type:	white braid
Cable length [m]:	1.50
Number on the palette [pcs]:	416
Dimensions of single box [mm]:	fi=90mm L=335mm
Net weight [kg]:	0.600
Gross weight [kg]:	0.700
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	<u>51/2025</u>
Manual:	Download PDF

Card creation date: 23 May 2025



